

Printing date 29.03.2017

Version number 4

Revision: 28.03.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: OEST SPEZIAL-GETR.ÖL V 500 A · Article number: 37266 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Lubricating oil · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Georg Oest Mineraloelwerk GmbH & Co. KG Georg - Oest - Str. 4 D-72250 Freudenstadt Tel.: +49 (0) 7441 / 539-0 · Further information obtainable from: Tel.: +49 (0) 7441 / 539 - 0 e-mail: productsafety@oest.de · 1.4 Emergency telephone number: Tel.:+49 (0) 7441 / 539 - 0 (08:00 a.m. - 5:00 p.m.) or European emergency call 112 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture

• *Classification according to Regulation (EC) No 1272/2008* The product is not classified according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- Additional information:
- The mineral oils in this product contain < 3% DMSO-extract (IP 346).

EUH208 Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl, Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

(Contd. on page 2)

oest

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.03.2017

Version number 4

Revision: 28.03.2017

Trade name: OEST SPEZIAL-GETR.ÖL V 500 A

	(Co	ontd. of page 1)	
EC number: 931-384-6	Reaction products of 4-methyl-2-pentanol and diphosphorus	1-<2.5%	
Reg.nr.: 01-2119493620-38			
	pentaoxide, and salted by amines, C12-14- tert-alkyl		
	Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Sens. 1, H317		
EC number: 939-460-0	Reaction product of 1,3,4-thiadiazolidine-2,5-dithione,	0.1-<1%	
Reg.nr.: confidential	formaldehyde and phenol, heptyl derivs.		
	� Flam. Liq. 3, H226; � Eye Dam. 1, H318; � Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412		
CAS: 112-90-3	(Z)-octadec-9-enylamine	0.25-<1%	
EINECS: 204-015-5 Index number: 612-283-00-3	 STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; STOT SE 3, H335 		

· Additional information:

SCL for EG 931-384-6: At concentrations < 50% no eye damage/irritations would be expected. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: No special measures required.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- \cdot 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 3)

Version number 4

Trade name: OEST SPEZIAL-GETR.ÖL V 500 A

(Contd. of page 2)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling No special measures required.

· Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- Storage class: 10

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

	rus pentaoxide, and salted by an DNEL longterm, systemic effect	0.25 mg/kg (General population)
	DNEL longterm, systemic effect	
		6.25 mg/kg (General population)
Inhalative	DNEL longterm, systemic effect	8.56 mg/m^3 (Workers)
		2.2 mg/m ³ (General population)
Reaction p	roducts of 4-methyl-2-pentanol rus pentaoxide, and salted by an	and diphosphorus pentasulfide, propoxylated, esterified with nines, C12-14- tert-alkyl
Reaction p diphosphor		
Reaction p diphosphor	rus pentaoxide, and salted by an	
Reaction pr diphosphor PNEC	<i>us pentaoxide, and salted by an</i> 0.00012 <i>mg/l (marine water)</i>	
Reaction p diphosphor PNEC PNEC STP	rus pentaoxide, and salted by an 0.00012 mg/l (marine water) 0.0012 mg/l (freshwater)	
Reaction p diphosphor PNEC PNEC STP	<i>rus pentaoxide, and salted by an</i> 0.00012 mg/l (marine water) 0.0012 mg/l (freshwater) 24.33 mg/l (-)	nines, C12-14- tert-alkyl
diphosphor PNEC PNEC STP	<i>us pentaoxide, and salted by an</i> 0.00012 mg/l (marine water) 0.0012 mg/l (freshwater) 24.33 mg/l (-) 2.54 mg/kg (soil)	nines, C12-14- tert-alkyl water))

· 8.2 Exposure controls

· Personal protective equipment:

• General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

• Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

(Contd. on page 4)

GB



Printing date 29.03.2017

Version number 4

Revision: 28.03.2017

Trade name: OEST SPEZIAL-GETR.ÖL V 500 A

(Contd. of page 3)

GB

· Protection of hands:

Printing date 29.03.2017



Protective gloves

 \cdot Material of gloves Nitrile rubber, NBR

· Penetration time of glove material

longterm contact:

NBR: thickness:0,425 mm; break trough: 240 - 480 min. shortterm contact:

NBR: thickness 0,12; break trough: 10 - 30 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Goggles recommended during refilling

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Fluid Form: Brown Colour: Characteristic · Odour: · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** Undetermined. 210 °C (DIN ISO 2592) · Flash point: · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Decomposition temperature: Not determined. · Self-igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: Not determined. Lower: Not determined. Upper: · Vapour pressure: Not determined. · Density: 0.91 g/cm3 15 °C (DIN 51757) · Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not determined. (Contd. on page 5)



Printing date 29.03.2017

Version number 4

Revision: 28.03.2017

Trade name: OEST SPEZIAL-GETR.ÖL V 500 A

		(Contd. of page
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octano	/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	430 mm ² /s 40 °C (DIN 51562T1)	
· Solvent content:		
Organic solvents:	0.0~%	
VÕC (EC)	0.00 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Oral LD50 2000 mg/kg (rat) (OECD 401)

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on human repeat insult patch test (HRIPT)

Based on human repeat insult patch test (HRIPT) and based on experience dermal sensitisation is not expected to be observed.

- Toxicokinetics, metabolism and distribution No further relevant information available.
- *Repeated dose toxicity No further relevant information available.*
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- No further relevant information available.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)

GR

[·] Primary irritant effect:

[·] Skin corrosion/irritation Based on available data, the classification criteria are not met.

Version number 4

Revision: 28.03.2017

Trade name: OEST SPEZIAL-GETR.ÖL V 500 A

(Contd. of page 5) **SECTION 12: Ecological information** · 12.1 Toxicity · Aquatic toxicity: Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl *EC50* 6.4 *mg/l* (algae) (*OECD* 201) 91.4 mg/l (daphnia) (OECD 202) 24 mg/l (fish) (OECD 203) NOEC 0.12 mg/l (daphnia) (OECD 211) 112-90-3 (Z)-octadec-9-enylamine EC50 0.03 mg/l (algae) (96 h) 0.011 mg/l (daphnia) (48 h) 0.11 mg/l (fish) (96 h) · 12.2 Persistence and degradability No further relevant information available. · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available. · Additional ecological information: · General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Based on ecotoxicological tests of similar mixtures this product is not classified as hazardous for the environment. · 12.5 Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. · 12.6 Other adverse effects No further relevant information available. **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

• *Recommendation Must be specially treated adhering to official regulations.*

· European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

15 01 10* packaging containing residues of or contaminated by hazardous substances

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

14.1 UN-Number		
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	



Printing date 29.03.2017

Version number 4

Trade name: OEST SPEZIAL-GETR.ÖL V 500 A

		(Contd. of page 6)
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group	1011	
· ADR, IMDG, IATA	Void	
 14.5 Environmental hazards: Marine pollutant: 	No	
-		
• 14.6 Special precautions for user	Not applicable.	
• 14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases H226 Flammable liquid and vapour.

H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. · Department issuing SDS: productsafety@oest.de · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent



Printing date 29.03.2017

Revision: 28.03.2017

GB

Version number 4

Revision: 28.03.2017

Trade name: OEST SPEZIAL-GETR.ÖL V 500 A

LD50: Lethal dose, 50 percent *PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative* Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \cdot * Data compared to the previous version altered.



Printing date 29.03.2017

(Contd. of page 7)